



Danfoss - VLT FC 302 Automation Drives

FC-302N315T5135X4732H2BGXXXXSXXXXAXBXCXXXXDX



In Stock, Shipping Varies

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302N315T5135X4732H2BGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Control Terminal Cross Section (Collar End Sleeves): 0.5 mm² (20 AWG)
Dimensions: 200x150x100 mm
Max Motor Cable Length (Screened): 150 m
Operating Voltage: 200-240 VAC
Relay 1 Output Terminals: NC: 1-3, NO: 1-2
Weight: 3 kg

Control Terminal Cross Section (Flexible): 1.5 mm² (16 AWG)
Efficiency: 85%
Max Motor Cable Length (Unscreened): 300 m
Protection Rating: IP55
Relay 2 Output Terminals: Break: 4-6, Make: 4-5
Last Verified: 05/11/2025 3:04 AM

Control Terminal Cross Section (With End Sleeves): 1 mm² (18 AWG)
Frequency: 50/60 Hz
Minimum Control Terminal Cross Section: 0.25 mm² (24 AWG)
Rated Power: 500 W
Speed: 3000 RPM

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods

