

Danfoss - VLT FC 302 Automation Drives

FC-302N355T5135N9862H2XGXXXXSXXXAXBXCXXXDX



In Stock, Shipping Varies

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



6

@

Secure Online Checkout Free Ground Shipping One Year Warranty

The FC-

302N355T5135N9862H2XGXXXSXXXAXBXCXXXDX is a part of the VLT FC 302 Automation Drives Series by Danfoss.

Specifications

| Control Interface: | RS-485 Modbus, Profibus DP | Cooling Method: | Forced air cooling | Dimensions: | 200 x 150 x 75 mm |
|---------------------------|-------------------------------|---------------------------------|--|----------------------|----------------------|
| Efficiency: | 95% | Enclosure Material: | Metal with corrosion- resistant finish | Harmonic Distortion: | Less than 3% |
| Input Frequency Range: | 50-60 Hz | Installation Altitude: | Up to 2000 meters without derating | IP Rating: | IP20 |
| Maximum Current: | 10A | Operating Temperature Range: | -20°C to +50°C | Output Voltage: | 450V |
| Overload Protection | n: ^{Yes} | Switching Frequency: | Adjustable up to 16 kHz | Weight: | 2.5 kg |
| Last Verified: | 05/10/2025 9:25 PM | | | | |

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- <u> Fax: 1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.