



Danfoss - VLT FC 302 Automation Drives

FC-302N450T5135U2356H2XGXXXXSXXXXAXBXCXXXXDX



In Stock, Shipping Varies



- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302N450T5135U2356H2XGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Ambient Operating Humidity:	5% to 95% non-condensing	Braking Options:	Built-in DC chokes and optional dynamic braking module	Communication Protocols:	Modbus RTU, Profibus, Ethernet/IP
Control Type:	Vector control, Closed-loop control	Cooling:	Forced air cooling	Efficiency:	Up to 98%
EMC Performance:	Complies with EN 61000-6-2, EN 61000-6-4	Input Voltage Range:	380-480 V AC	Mounting Options:	Wall-mount, panel-mount
Output Frequency:	0-500 Hz	Power Rating:	1.5 kW to 2.8 MW	Programmable Inputs/Outputs:	3 programmable relay outputs, 5 digital inputs
Protection Class:	IP20, IP21, IP54	Safety Features:	Safe Torque Off (STO), Overcurrent, Earth fault protection	Thermal Management:	Integrated temperature monitoring and control
Last Verified:	05/10/2025 10:48 AM				

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods

