

Danfoss - VLT FC 302 Automation Drives

FC-302P11KT2131X7357H2BGXXXXSXXXXAXBXCXXXXDX Request a Quote

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer

Secure Online
CheckoutFree Ground
ShippingOne Year
Warranty

The **FC-302P11KT2131X7357H2BGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

| | | | | | |
|--------------------------------|--------------------------|--------------------------|---------------------------|-----------------------------|--------------------------|
| Communication Protocol: | Modbus RTU | Control Type: | Analog and Digital Inputs | Cooling Method: | Forced Air |
| Dimensions: | 390 mm x 150 mm x 245 mm | Emc Filtering: | Integrated | Enclosure Rating: | IP21 |
| Input Voltage Range: | 380-480 V | Installation Kit: | NEMA Type 1 | Motor Control: | V/Hz and VVC+ |
| Overload Capacity: | 110% for 1 minute | Power Output: | 11 kW | Protection Features: | Overcurrent, Overvoltage |
| Switching Frequency: | 4-32 kHz | Weight: | 7.5 kg | Last Verified: | 06/02/2025 1:30 AM |

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA Toll Free: [1-888-551-3082](tel:1-888-551-3082) International: [1-919-443-0207](tel:1-919-443-0207) Fax: [1-919-867-6204](tel:1-919-867-6204) Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.