



Danfoss - VLT FC 302 Automation Drives

FC-302P1K1A2131B0407H2XGXXXXSXXXXAXBXCXXXXDX



In Stock, Shipping Varies



- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302P1K1A2131B0407H2XGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Ambient temp range:	0 to 45 C	Cable cross-section for mains, motor, brake:	12, 12, 12 AWG	Continuous output current:	2.7 to 6.6 A
Dimensions:	268 x 90 x 205 mm	Efficiency:	96 percent	Emc Level:	Class A
Energy efficiency:	IE2	max THD:	0.1	Maximum Temperature:	50°C
Motor output frequency range:	0 to 590 hz	Motor output frequency range (flux mode):	0 to 300 hz	Power Loss:	58 to 63 watts
Rated Leakage Current:	3.5 mA	Supported supply frequency:	50/60 Hz	Weight:	4.9 kg
Last Verified:	05/09/2025 3:17 AM				

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods

