

Danfoss - VLT FC 302 Automation Drives

FC-302P1K5T5E20H1XXXXXXXXS001XANBXCXXXXDX

 **In Stock, Ships Fast**



- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302P1K5T5E20H1XXXXXXXXS001XANBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

| | | | | | |
|-------------------------------|------------------------|---------------------------|-----------------|-----------------------------|---|
| Communication Options: | Profibus | Control Principle: | VVC+ | Cooling: | Air Cooled |
| Current: | 3 A | Enclosure: | IP20 | Frequency Range: | 0-500 Hz |
| Inputs: | 8 digital, 2 analog | Mains Option: | No mains option | Outputs: | 2 digital, 1 analog Overcurrent, Overvoltage, Undervoltage |
| Phase : | Three Phase | Power Rating: | 1.5 kW | Protection Features: | 8 kg |
| Temperature Range: | -10 to 50 °C | Voltages: | 380-480 V | Weight: | |
| Last Verified: | 05/09/2025 11:47 AM | | | | |

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.