



Danfoss - VLT FC 302 Automation Drives

FC-302P2K2A2131B0409H2XGXXXXSXXXXAXBXCXXXXDX



In Stock, Shipping Varies

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty



The **FC-302P2K2A2131B0409H2XGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Cable cross-section for mains, motor, brake:	12, 12, 12 AWG	Continuous output current:	5.6 A	Dimensions:	268 x 90 x 205 mm
Efficiency:	0.97	Emc Level:	Class A	Maximum Temperature:	50°C
Motor output frequency (flux mode):	0 to 300 hz	Motor output frequency (VVC):	0 to 590 hz	Overloading torque:	110% of the nominal torque
Power Loss:	88 W	Rated Leakage Current:	3.5 mA	System frequency:	50/60 Hz
Typical shaft output:	2.2 kW	Typical shaft output (hp):	3 hp	Weight:	4.9 kg
Last Verified:	05/09/2025 8:15 PM				

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.