

Danfoss - VLT FC 302 Automation Drives

FC-302P3K0T5E20H2BGXXXXSXXXXAXBXCXXXXD0



 **In Stock, Ships 2-3 Days**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302P3K0T5E20H2BGXXXXSXXXXAXBXCXXXXD0** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Brake:	with brake chopper	Coating PCB:	none	Continuous input current:	6.5 A
Continuous output current:	7.2 A	Dimensions:	268 x 130 x 205 mm	Display:	GLCP
Efficiency:	0.97	Enclosure Sizes:	A2	Ip Rating:	IP20
Mains Voltage:	380-500 VAC	Operating Temperature Range:	32 to 122 deg F	RFI filter:	H2
Storage/Transport temperature:	(-13 to 149 deg F)	Typical shaft output:	3 kW	Weight:	6.6 to 7 kg
Last Verified:	05/09/2025 5:23 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.