

Danfoss - VLT FC 302 Automation Drives

FC-302P4K0T5131B0070H2BGXXXXSXXXXAXBXCXXXXDX

 **In Stock, Shipping Varies**



- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302P4K0T5131B0070H2BGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Communications:	RS485 serial communication interface	Control Card:	Standard Control Card with Safe Torque Off (STO)	Cooling:	Back channel cooling
Depth:	250 mm	Enclosure:	IP20, IP21, or IP55/NEMA 12	Harmonics:	Low harmonic emission
Height:	420 mm	Mains Supply Voltage:	200-240 V AC	Max Ambient Temperature:	50 °C
Power Size:	4 kW	Safety Features:	Safe Torque Off (STO)	Supply Voltage:	3 x 380-500 V
Weight:	10 kg	Width:	120 mm	Last Verified:	05/10/2025 7:44 PM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.