

Danfoss - VLT FC 302 Automation Drives

FC-302P55KT5131F0440H2XGXXXXSXXXXAXBXCXXXXDX

 **In Stock, Shipping Varies**



- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302P55KT5131F0440H2XGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Communication Protocols:	PROFIBUS, Modbus RTU, CANopen, EtherCAT	Compliance Standards:	CE, UL, cUL, RoHS, IEC 61800-3	Control Method:	Vector Control, V/f Control
Cooling Method:	Forced Air Cooling	Efficiency:	95%	Frequency Range:	0 - 400 Hz
Harmonic Mitigation:	Built-in DC Choke	Input Voltage:	230 VAC	Mounting Type:	DIN Rail Mountable
Operating Temperature Range:	-10C to 50C	Output Current:	7.2 A	Output Power:	1500 W
Overload Capacity:	150% for 1 minute	Programming Interface:	Graphical Display with Keypad	Protection Grade:	IP65
Last Verified:	05/09/2025 4:39 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

