



Danfoss - VLT FC 302 Automation Drives

FC-302P55KT6131G5885HXBGXXXXSXXXXAXBXCXXXXDX



In Stock, Shipping Varies



- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302P55KT6131G5885HXBGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

| | | | | | |
|----------------------------|----------------------------|---------------------------------------|---|-------------------------------------|-------------------------------------|
| Braking Chopper: | Integrated Dynamic | Certification: | ATEX | Control Methods: | Sensorless Vector, Flux Vector, V/f |
| Cooling Method: | Air Cooling with Heat Sink | Display Interface: | Detachable LCP, GUI | EMC Compliance: | IEC 61800? 3 C2/C3/C4 |
| Enclosure Material: | Polycarbonate | Fieldbus Protocols (Ethernet): | PROFINET, EtherNet/IP, POWERLINK, BACnet/IP | Fieldbus Protocols (Others): | DeviceNet, Modbus TCP |
| Ingress Protection: | IP67 | Motor Compatibility: | IM, PM, SynRM | Operating Temperature: | -40°C to +85°C |
| Output Power: | 5.5 kW (7.5 HP) | Overload Capacity: | 110% for 60s; 180% for 3s | Rated Current: | 16 A |
| Rated Voltage: | 480 VAC | Safety Functions: | STO, SS1 | Last Verified: | 05/09/2025 11:51 AM |

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods

