

Danfoss - VLT FC 302 Automation Drives

FC-302P75KT6131N4646HXBGXXXXSXXXXAXBXCXXXXDX

 **In Stock, Shipping Varies**



- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302P75KT6131N4646HXBGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Braking Capability:	Built-in dynamic braking transistor	Cross-section Of Conductor:	25 mm ²	Current:	80 A
Dimensions:	80 x 398 x 200 mm	Emc Level:	Class A	Frequency:	50/60 Hz
Ground Fault Protection:	Integrated ground fault detection and interruption	Installation:	Both vertical and horizontal orientations	Maximum Temperature:	45°C
Power Loss:	25 W	Rated Leakage Current:	35 mA	Standby Power Consumption:	Less than 10 W in standby mode
Switching Frequency Options:	Adjustable from 2 to 16 kHz	User Interface:	Detachable keypad with dual display (numeric and graphic)	Weight:	6 kg
Last Verified:	05/09/2025 3:44 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.