

Danfoss - VLT FC 302 Automation Drives

FC-302PK37A2134G1681H2XGXXXXSXXXXAXBXCXXXDX



an an p

96.0%

Free Ground Shipping

The Stock, Shipping Varies

One Year Warranty

302PK37A2134G1681H2XGXXXXSXXXXAXBXCXXXXDX is a part of the VLT FC 302 Automation Drives Series by Danfoss.

Specifications

| Continuous Kva (400 V Ac): | 0.9 kVA | Con V A Esti |
|---|-----------------------|--------------------|
| Enclosure Protection Rating: | IP20 | At F Loa |
| Intermittent (60 S Overload) Current: | 1.9 A | Ove Cur |
| Maximum Input Current Continuous (3x441 - 480 V): | 1.0 A | Out Con (3x3 |
| Phases: | 3-phases | Pov |
| Last Verified: | 05/10/2025 4:15 PM | FUV |

Continuous Kva (480 0.9 kVA .c): imated Power Loss Rated Maximum 20.9 W ad: ermittent (60 S erload) Input 1.9 A rrent: tput Current ntinuous 1.2 A 380**≕**440 V): 5.5 kW wer Rating:

Efficiency:

| Frequency Converter Typical Shaft Output: | 0.37 kW (0.5 hp) |
|---|------------------|
| Maximum Input Current Continuous (3x380=440 V): | 1.2 A |
| Output Current Continuous (3x441===4480 V): | 1.1 A |
| Weight, Enclosure Protection Rating Ip20: | 2.3 kg (5.1 lb) |

Contact Us

- 1620 Old Apex Road, Cary, NC 27513, USA
- Toll Free: 1-888-551-3082
- International: <u>1-919-443-0207</u>
- Fax: 1-919-867-6204
- Email: sales@automation-factory.com

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.