

Danfoss - VLT FC 302 Automation Drives

FC-302PK37T2131X7321H2BGXXXXSXXXXAXBXCXXXXDX

 **In Stock, Shipping Varies**



- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302PK37T2131X7321H2BGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

12-pulse Drive:	3 x 380-500 V, 250 kW - 1 MW	Ambient Conditions:	Standard industrial environment	Analog Input:	0-20 mA and 4- 20 mA
Brake Resistor Option:	40% overload	Control Card Output Voltage:	+10 V DC	Efficiency:	High-efficiency drive
Enclosure Sizes:	K1 to K5	Height (motors With Ip21 Kit):	338.5 - 520 mm	Ip Rating:	IP20/IP21
Low Harmonic Drive:	3 x 380-480 V, 132-450 kW	Motor Speed:	Standard variable speed range	Power Range:	0.37 kW - 1.1 MW
Rs485 Serial Communication:	Supported	Supply Voltage:	3 x 380-500 V	Weight:	2.5 to 11.5 kg
Last Verified:	05/10/2025 1:57 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.