



Danfoss - VLT FC 302 Automation Drives

FC-302PK75T5131X7334H2BGXXXXSXXXXAXBXCXXXXDX



In Stock, Shipping Varies



- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **FC-302PK75T5131X7334H2BGXXXXSXXXXAXBXCXXXXDX** is a part of the **VLT FC 302 Automation Drives Series** by **Danfoss**.

Specifications

Circuit Breakers:	Moeller type recommended	Control Cable Cross-Section:	Maximum: 1.5 mm ² (16 AWG) for flexible/rigid wire	Front Cover Tightening Torque:	Plastic Cover: Click mechanism
Interface Type:	Ethernet	Motor Thermal Protection:	Thermistor trip or warning	Motor Types Supported:	Asynchronous motors (ASM)
Mounting Style:	Panel Mount	Operating Voltage:	120-240 VAC	Output Power:	500 W
Safe Torque Off (STO):	Terminal 37: 0SP#24 V DC	Scan Interval:	1 ms	Speed Control Range:	Open Loop: 1:100 of synchronous speed
Starting Torque:	Maximum 160% for 60 s (constant torque)	Temperature Range:	0°C to 70°C	USB Ground Connection:	Not galvanically isolated from protective earth
Last Verified:	05/10/2025 2:47 PM				

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

🌐 International: [1-919-443-0207](tel:1-919-443-0207)

📠 Fax: [1-919-867-6204](tel:1-919-867-6204)

✉ Email: sales@automation-factory.com

Shipping Options



Payment Methods

