



Kollmorgen - H Hybrid Motors

H22NREC-LDN-NS-00



 Request a Quote

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **H22NREC-LDN-NS-00** is a part of the **H Hybrid Motors Series** by Kollmorgen.

Specifications

Construction Type:	Splashproof	Electrical Connection:	Conduit with removable insulating bushing	Encoder Provision:	Built-in encoder option
Frame Configuration:	NEMA 42	Front Shaft Configuration:	Standard round mounting	L1 Maximum Length:	5.61 in [142.5 mm]
L2 Length:	4.85 in [123.2 mm]	Max Holding Torque:	239 oz?in	Max Radial Shaft Force:	35 lb
Mounting Hole Bolt Circle:	Ø3.000 in [76.2 mm], equally spaced	Precision Bore Diameter:	Ø2.186 ±0.002 in [55.52 ±0.05 mm]	Rotor Inertia:	0.0083 oz?in?s^2
System Interface:	MS Connector (C)	Terminal Board Connections:	Type L or M	Thermal Resistance:	3.9 °C/W
Last Verified:	06/05/2025 7:32 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.