

Kollmorgen - H Hybrid Motors

H32NRFA-LNN-NS-00



 **In Stock, Shipping Varies**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **H32NRFA-LNN-NS-00** is a part of the **H Hybrid Motors Series** by **Kollmorgen**.

Specifications

Application Documentation:	Heavy-duty option guides included	Back Shaft Configurations:	Includes options with flat, key, or customized designs	Base Circle Connection (thread):	3X #10-32 UNC-2B (minimum depth 0.25 inches)
Conduit Connection Dimension (I Construction):	1/2 NPSC Tap with 0.56 inches insulating bushing	Conduit Connection Dimension (m Construction):	PG 13.5 Tap without insulating bushing	Diameter At Base Circle:	3.000 inches [76.2 mm]
Encoder Connector:	Included for Encoder Mounting Option	Front Shaft Configuration:	Multiple standard options available	Input Power Wiring:	#22 AWG minimum for 8-lead motors
Material Standard Compliance:	NEMA 34 Frame Dimension Standards	Mounting Configuration:	Standard Round Mounting (not available on 3 stack motor)	Splashproof Construction Option:	Available with Terminal Board Connections
Total Length (I1 Max):	6.73 inches [170.94 mm]	Total Length (I2):	5.61 inches [142.49 mm]	Weight (approx.):	(Refer to specific configuration)
Last Verified:	06/04/2025 3:03 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

