



Kollmorgen - H Hybrid Motors

H33NREC-LDN-NS-00



In Stock, Ships Today

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **H33NREC-LDN-NS-00** is a part of the **H Hybrid Motors Series** by Kollmorgen.

Specifications

Axial Shaft Loading Force: 180 lb (801 N)

Dimension L2: 5.61 inches (142.49 mm)

Mounting Configuration: Standard Round Mounting - Not available on 3-stack motor

Radial Shaft Loading Force: 35 lb (156 N)

Splashproof Construction Options: Terminal Board or MS Connector

Last Verified: 06/06/2025 2:40 AM

Construction Type:

Encoder Connector Removal:

Phase Inductance:

Rated Current/phase:

Thermal Resistance:

Conventional Hybrid Motor, NEMA Compatible Frame

Includes removable insulating bushing

1.0 mH (Series Typical)

Varies, e.g., 8.4A for H31xxHP-L Series

3.9 °C/Watt

Dimension L1 Max:

Max Encoder Mounting Option:

Phase Resistance:

Rotor Inertia:

Weight:

6.73 inches (170.94 mm)

0.71 inches (18.04 mm)

Typical 0.13 Ohms (Parallel)

0.0083 oz-in-s² (0.0586 kg-m² x 10⁻³)

3.2 lb (1.45 kg)

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods

