

Kollmorgen - Kollmorgen Servo Cables

ENC-AKM-030M-MCS-DCA-28-NA



 [Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **ENC-AKM-030M-MCS-DCA-28-NA** is a part of the **Kollmorgen Servo Cables Series** by **Kollmorgen**.

Specifications

Cable Shielding:	Dual-shielded with foil and braid	Command Input:	Analog velocity or torque, 0 to +10V	Connector Durability:	Rated for 500 mating cycles
Continuous Output Current:	3.0A for MMC-SD-1.3-460 and 5.5A for MMC-SD-2.4-460	Dc Input Voltage Range:	24VDC +15% -10%	Fire Resistance:	UL VW-1 flame retardant
General Purpose Inputs:	8 optically isolated 24V DC inputs, active high	General Purpose Outputs:	4 optically isolated 24VDC outputs, active high	Input Frequency:	47-63Hz
Nominal Input Power:	1.94kVA for MMC-SD-1.3-460 and 3.33kVA for MMC-SD-2.4-460	Nominal Input Voltage:	207-460 VAC, Three Phase	Output Frequency:	0-450Hz
Peak Output Current:	6.0A for MMC-SD-1.3-460 and 11.0A for MMC-SD-2.4-460	Typical Input Current:	700mA	Weight:	10 lbs
Last Verified:	05/07/2025 9:06 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

