

Kollmorgen - Kollmorgen Servo Cables

M.1301.3911



 **In Stock, Shipping Varies**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **M.1301.3911** is a part of the **Kollmorgen Servo Cables Series** by Kollmorgen.

Specifications

AC Input Frequency:	47-63 Hz	AC Input Voltage Limits:	180-528 VAC	AC Input Voltage Nominal:	200-480 VAC
Analog Input Resolution:	14-bit (± 10 V)	Commutation Method:	3-phase sinusoidal SVM	Continuous Output Current (size 3):	36.5 A (0-peak)
Continuous Power Output:	Up to 8.0 kW	Current Regulator Update Rate:	125 μ s	DC Input Inrush Current:	4 A (10 ms)
DC Input Typical Current:	1050 mA		8 x 24 V DC opto-isolated		4 x 24 V DC opto-isolated (short-circuit protected)
Energy Absorption Capability:	Up to 44 J (460 V input)	Digital Inputs:		Digital Outputs:	
Operating & Storage Temperature:	0-50 °C op; -30-70 °C storage	External Shunt Power (size 3):	29 kW	External Shunt Resistance (size 3):	22 ?
Velocity Regulator Update Rate:	250 μ s	Peak Output Current:	Up to 73 A (0-peak)	Physical Weight:	35 lbs (15.9 kg)
		Last Verified:	07/25/2025 5:50 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

