

Kollmorgen - Kollmorgen Servo Cables

M.1302.8286



 [Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **M.1302.8286** is a part of the **Kollmorgen Servo Cables Series** by Kollmorgen.

Specifications

Bend Radius:	Minimum bend radius of 5 times the cable diameter	Cable Length:	0.6 M (2.0 ft)	Cable Type:	28 AWG, shielded, twisted pair, 8 conductor
Connectors:	8-Pin RJ-45 Plug (to Digital Link Port and to Digital Drive)	Durability:	Rated for 1,000,000 flex cycles	EMI Protection:	Aluminum Mylar shielding with drain wire
Impedance:	100 Ohms \pm 15%	Operating Temperature Range:	-20°C to +80°C	Receive Data -:	Pin 6 (to Digital Link Port), Pin 6 (to Digital Drive)
Receive Data +:	Pin 3 (to Digital Link Port), Pin 3 (to Digital Drive)	Shell Drain:	Shell	Signal Attenuation:	Less than 0.6 dB per meter at 1 MHz
Transmit Data -:	Pin 2 (to Digital Link Port), Pin 2 (to Digital Drive)	Transmit Data +:	Pin 1 (to Digital Link Port), Pin 1 (to Digital Drive)	Voltage Rating:	300V
Last Verified:	05/07/2025 4:01 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

