

Kollmorgen - Kollmorgen Servo Cables

MK 6SM27/37/47/57/77



 **In Stock, Shipping Varies**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **MK 6SM27/37/47/57/77** is a part of the **Kollmorgen Servo Cables Series** by Kollmorgen.

Specifications

Approvals:	UL Recognized, CSA Certified, CE Marked	Bend Radius:	Minimum 10 times the cable diameter	Cable Length:	10 m
Cable Type:	Flexible, shielded power cable	Conductor Material:	Stranded tinned copper	Connector Specification:	92179 IC 4G1.0 + 1x2x1
Connector Type:	Rundstecker female M23, 9-pin	Insulation Standard (awm Style):	E73526 RU AWM 80°C, 1000V, STYLE 20940	Insulation Standard (csa Awm):	LL88673 CSA AWM I/II A/B, 75°C, 1000V, FT1
Jacket Material:	PVC (Polyvinyl Chloride)	Nominal Current:	4 x 1 A + (2 x 0,75 A)	Oil Resistance:	Compliant with Oil Res I/II standards
Shielding:	Overall braided shield with foil for EMI/RFI protection"	Temperature Range:	-40°C to +80°C	Voltage Rating:	1000 V
Last Verified:	07/26/2025 12:48 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.