



Kollmorgen - Kollmorgen Servo Cables

PWR-AKM-009M-MCS-000-12-6H



[Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PWR-AKM-009M-MCS-000-12-6H** is a part of the **Kollmorgen Servo Cables Series** by **Kollmorgen**.

Specifications

Bend Radius (static/dynamic):	90/144 mm	Brake Option:	24V Holding Brake	Cable Jacket Material:	PUR or PVC
Cable Type:	4-conductor + shield servo cable	Cable Voltage Rating:	1000V	Certification Standards:	CE, CEI 20-35, NFPA 79, UL/ULC
Connector Type:	M23 or M40	Feedback Type:	SFD3 / Resolver / EnDat / HIPERFACE DSL®	Main Conductor Size:	6 mm ²
Maximum Cross Section (power/signal):	16/4 mm ²	Maximum Current (power/signal):	75/30 A	Operating Cycles:	10 million at minimum bend radius factor (F x DIA)
Protection Class:	IP65	Temperature Range:	-15°C to +70°C	Weight:	0.589 kg/m (approx.)
Last Verified:	09/05/2025 5:02 AM				

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.