



Kollmorgen - Kollmorgen Servo Cables

PWR-AKM-015M-MCS-000-16-6H



[Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PWR-AKM-015M-MCS-000-16-6H** is a part of the **Kollmorgen Servo Cables Series** by **Kollmorgen**.

Specifications

Cable Length Customization: up to 25 m

Cable Temperature Rating: 80 °C

Dynamic Bend Radius (6 mm²): 144 mm

Length Increment Requests: user defined

Static Bend Radius (6 mm²): 90 mm

Last Verified: 09/04/2025
1:48 PM

Cable Material:

Certificate Standards:

Feedback Compatibility:

Life Cycle:

Voltage Rating:

PUR (Polyurethane) / PVC (Polyvinyl Chloride)

CE, Lead Free, Silicone-Free, NFPA 79

EnDat 2.2, HIPERFACE DSL

10 million cycles

1000 V

Cable Outer Diameter:

18 mm

Conductor Cross-section:

6 mm²

Ingress Protection Rating:

IP65

Operating Temperature Range:

-15 °C to +70 °C

Weight per Meter:

0.589 kg/m (0.396 lb/ft)

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3082](tel:1-888-551-3082)

International: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204)

Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.