

Kollmorgen - MMC Standalone Smart Drives

M.3000.0464

Specifications



<table-of-contents> In Stock, Shipping Varies

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Free Ground Shipping

One Year Warranty

The **M.3000.0464** is a part of the **MMC Standalone Smart Drives Series** by **Kollmorgen**.

AC Input Voltage Nominal:	400 VAC	AC Input Voltage Range:	207-528 VAC	Continuous Output Current:	3.0 A RMS
Continuous Output Power:	1.3 kW	DC Input Voltage Range:	24 V DC +15% / -10%	Energy Absorption Capacitance:	110 ?F
Holding Brake Driver Max Current:	0.5 A	Input Configuration:	Direct earthed star point (TN/TT mains)	Input Frequency:	47-63 Hz
Input Phase:	3-phase	Maximum Inrush Current:	4.56 A RMS	Nominal Input Current:	2.44 A RMS
Nominal Input Power:	1.94 kVA	Output Frequency Range:	0-450 Hz	Peak Output Current:	6.0 A
Shunt Switch Threshold:	780 V DC	Typical Input Current:	700 mA	Last Verified:	05/07/2025 5:13 AM

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- 둼 Fax: <u>1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.