

Kollmorgen - MMC Standalone Smart Drives

MMC-D32



 **In Stock, Ships Today**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online Checkout



Free Ground Shipping




One Year W

The **MMC-D32** is a part of the **MMC Standalone Smart Drive** by **Kollmorgen**.

Specifications

Application Memory:	3 MB	Battery Life:	?? years (power?off)	Battery Type:	3 V BR3032 coin cell
Block I/O Cable Length:	max 61 m (200 ft)	Block I/O Modules:	1??77 modules	Communication Ports:	1 PicPro RS232 (<=115.2 kbaud); 1 user RS232/ (RTS/CTS)
CPU:	600 MHz Celeron ULV, numeric coprocessor	Data Memory:	192 KB	Digital Link Ports:	100Base?TX (IEEE 802.3u), max cable 30 m
Ethernet Port:	10/100Base?TX half?duplex, max cable 50 m	Input Voltage:	20??30 VDC (24 VDC nominal)	Max Input Current:	1 A
Operating Temperature:	5 °C to 55 °C	RAMDISK Memory:	960 KB	Servo Axes Update Rates:	Up to 32 axes @ 1??8 ms; 24 axes @ 0.5 ms; 8 axes
Shock:	4 shocks/axis @ 15 g, 11 ms	Storage Temperature:	?40 °C to 85 °C	Time?of?Day Clock Accuracy:	±1 s/day @25 °C; +2/??12 s/day other
Vibration:	10??57 Hz @ 0.15 mm; 57??2000 Hz @ 2 g	Last Verified:	07/26/2025 5:09 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.