



Kollmorgen - S400 Servo Drives

PER-SERVOSTAR 403A-C



 [Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PER-SERVOSTAR 403A-C** is a part of the **S400 Servo Drives Series** by Kollmorgen.

Specifications

Ambient Temperature with Derating:	+45°C to +55°C (2.5%/K derating)	DC Bus Link Voltage:	160 V to 560 V DC	Enclosure Protection:	IP 20
Input Voltage Range:	±10 V	Input Voltage Resolution:	14-bit	Maximum Motor Cable Length:	25 m
Operating Ambient Temperature:	0°C to +45°C (full rating)	Operating Humidity:	78% RH, non-condensing	Output Stage Clock Frequency:	8 kHz (optional 16 kHz)
Output Stage Dissipation at Rated Current:	30 W to 40 W	Overvoltage Trip Threshold:	450 V to 750 V (model dependent)	Peak Output Current:	9 A RMS, 5 s
Quiescent Power Dissipation:	12 W to 15 W	Rated Output Current (RMS):	3 A RMS, ±3% @ 8 kHz	Rated Supply Voltage:	1×115V-10% to 3×230V+10% or 3×400V+10%
Weight:	3 kg	Last Verified:	09/05/2025 4:32 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.