

Okuma - BL Servo Motors

BL-MC150J-12TNA



Request a Quote

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer

Secure Online
Checkout

Ω

Free Ground Shipping One Year Warranty

The **BL-MC150J-12TNA** is a part of the **BL Servo Motors Series** by **Okuma**.

Specifications

Control Compatibility:	Okuma CNC controllers	Encoder (1000-line):	3 V/1000 rpm ±20%	Encoder (500-line):	1.5 V/1000 rpm ±20%
Feedback Cable:	Detachable at motor end	Installation:	Retrofit for Okuma servo systems	Motor Cable:	5 leads to 5?way screw terminal
Motor Type:	Positioning servo, high dynamic response	Operating Environment:	Factory floor conditions	Rated Voltage:	12 V DC nominal
Tachometer Output:	06/03/2025	Terminal Cover Removal:	Loosen 4 retaining bolts	Torque Direction:	CW when V1 > V2
Last Verified:	5:12 PM				
	Compatibility: Feedback Cable: Motor Type:	Compatibility:controllersFeedback Cable:Detachable atFeedback Cable:Detachable atMotor Type:responseMotor Type:User I/O Pin 7Tachometer Output:for velocity06/03/2025	Compatibility:controllersEncoder (1000-line):Feedback Cable:Detachable at motor endInstallation:Positioning servo, high dynamicOperating Environment:Motor Type:responseEnvironment:User I/O Pin 7 for velocity 06/03/2025Terminal Cover Removal:	Compatibility:controllersEncoder (1000-line):3 V/1000 rpm ±20%Feedback Cable:Detachable at motor end Positioning servo, high dynamicInstallation:Retrofit for Okuma servo systemsMotor Type:responseEnvironment: User I/O Pin 7 for velocity 06/03/2025Detachable at motor end Positioning servo, high dynamicServo systemsMotor Type:responseEnvironment: Environment: User I/O Pin 7 for velocity 	Compatibility:controllersEncoder (1000-line):3 V/1000 rpm ±20%Encoder (500-line):Feedback Cable:Detachable at motor end Positioning servo, high dynamicInstallation:Retrofit for Okuma servo systemsMotor Cable:Motor Type:Positioning responseOperating Environment: User I/O Pin 7 for velocity 06/03/2025Operating Removal:Rated Voltage:Tachometer Output:Detachable at motor end Positioning servo, high dynamicTerminal Cover Removal:Loosen 4 retaining boltsRated Voltage:

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- 둼 Fax: <u>1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.