

Okuma - E4809 CNC Boards





Specifications

Actuation Speed:	Approximately 2 seconds per stroke	Components:
Current Draw:	2.5 A	Dimensions:
Material:	Stainless Steel construction	Mounting Type:
Part Code:	E4809-045-047-C	Pressure Rating:
Resistors:	Included	Voltage Rating:
	06/04/2025	
Last Verified:	6:41 AM	

•	Request a Quote
---	-----------------

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer

÷
Secure Online

Checkout

Free Ground Shipping

One Year Warranty

The **E4809-045-047-C** is a part of the **E4809 CNC Boards Series** by **Okuma**.

Integrated Capacitors		Modbus RTU communication
	Control Interface:	protocol
	Ingress Protection	IP67 for dust and
x 75 x 60 mm	(ip) Rating:	water resistance
Flanged mounting		
for secure	Operating	-20°C to 60°C
attachment	Temperature:	
Up to 150 psi	Protection Class:	IP65
• •		
230 VAC	Weight:	1.2 kg

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- 🤳 Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- 둼 Fax: <u>1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.