



Okuma - E4809 CNC Boards

E4809-045-131-A



 **In Stock, Shipping Varies**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **E4809-045-131-A** is a part of the **E4809 CNC Boards Series** by **Okuma**.

Specifications

Approvals:	RoHS Compliant	Bend Radius:	10x cable diameter minimum	Cable Diameter:	Typically 7-10 mm (exact size may vary by revision)
Connector A:	Circular, Standard	Connector B:	Circular, Standard	Length:	45 meters
Maximum Voltage:	300V	Operating Temperature Range:	-20°C to +80°C	Sheathing Material:	PVC (Polyvinyl Chloride)
Shielding:	Overall Braided Shield	Type:	Encoder Feedback Cable	Weight:	Approximated per meter basis (exact value on datasheet)
Last Verified:	08/16/2025 5:08 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.