


Okuma - E4809 CNC Boards

E4809-04U-005-B



 **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **E4809-04U-005-B** is a part of the **E4809 CNC Boards Series** by **Okuma**.

Specifications

Capacitors:	Electrolytic for filtering & noise reduction	Connectors:	Supports I2C and other communication protocols	Current Rating:	4 A
Dimensions:	50 x 30 x 20 mm	Display:	7-segment for diagnostics & error codes	Housing Material:	Aluminum
ICs:	Power regulation, signal processing, communication	Input Voltage:	480 V AC	Isolation Voltage:	1000 V
Operating Temperature:	-40°C to 85°C	Output Voltage:	5 V DC	Resistors & Diodes:	Surge protection & current control
USB Ports:	Type A, micro, mini for data transfer & power	Weight:	120 g	Last Verified:	06/04/2025 10:08 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.