Okuma - E4809 CNC Boards

E4809-770-086-E

🚚 **Request a Quote**

☑ Get a Quote in 5 minutes
☑ Parts ship in as little as 24 hours
☑ Up to half the cost of the manufacturer

🔒 Secure Online Checkout

🚚 Free Ground Shipping

⚙ One Year Warranty

The **E4809-770-086-E** is a part of the **E4809 CNC Boards Series** by **Okuma**.

Specifications

Capacitors:	Electrolytic and ceramic for filtering and decoupling	**Communication Interfaces:**	RS232, Ethernet	**Connectors:**	Ribbon (10-pin, 14-pin), D-sub-style headers
Dimensions:	Approximately 600 mm x 400 mm x 150 mm	**IC Types:**	HC245, HC244, HC14 (buffer, inverter logic)	**Input Frequency:**	50/60 Hz
Memory:	Approximately 256 MB DDR (typical)	**Mounting:**	4-screw hole configuration	**Mounting Type:**	Panel and Rack mount
Operating Temperature:	0°C to 50°C	**Operating Voltage:**	110/220 V AC (dual voltage)	**Processor:**	High-performance digital signal processor
Relays:	Omron G5V-1 style	**Silkscreen Labels:**	XB3, XB5, XB11, XB12	**Weight:**	Approximately 25 kg
Last Verified:	06/05/2025 5:07 AM				

Contact Us

📍 1620 Old Apex Road, Cary, NC 27513, USA

📞 Toll Free: 1-888-551-3082

🌐 International: 1-919-443-0207

📠 Fax: 1-919-867-6204

✉ Email: sales@automation-factory.com

Shipping Options

DHL   FedEx   UPS   (ocean freight)

Payment Methods

American Express   MasterCard   VISA   WIRE TRANSFER