



Okuma - E4809 CNC Boards

E4809-770-112-A



 [Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **E4809-770-112-A** is a part of the **E4809 CNC Boards Series** by **Okuma**.

Specifications

Connector Configuration:	96-pin (A1 ^{SFR} A32, B1 ^{SFR} B32, C1 ^{SFR} C32)	Connector Labels:	XB-1L, XB-2L, XB-3L, XB-4L	Connector Type:	DIN 41612
Mounting Format:	Plug-in for Okuma control systems	Operating Temperature:	0°C to 50°C (32°F to 122°F)	Power Input Voltage:	~12 VDC (regulated)
Relative Humidity:	20% to 85% (non-condensing)	Storage Temperature:	-10°C to 60°C (14°F to 140°F)	Last Verified:	06/04/2025 1:51 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.