



Okuma - E4809 CNC Boards

E4809-820-001-A



 [Request a Quote](#)

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **E4809-820-001-A** is a part of the **E4809 CNC Boards Series** by **Okuma**.

Specifications

Connector Type:	4-Pole Terminal Block	Current Rating:	820 A	Dielectric Strength:	2500 V
Dimensions:	150 x 100 x 75 mm	Enclosure Rating:	IP65 for dust and water ingress protection	Insulation Resistance:	Minimum of 1 M?
Mounting Orientation:	Horizontal/Vertical installation possible	Operating Frequency:	50/60 Hz	Overload Protection:	Includes thermal overload protection
Quality Standard:	ISO 9001 certified manufacturing process	Temperature Range:	-20C to 85C	Voltage Rating:	480 V AC
Weight:	Approximately 3.2 kg	Last Verified:	06/05/2025 2:06 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

