




Okuma - E4809 CNC Boards

PC-4018



 [Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout










Free Ground
Shipping



One Year
Warranty


The **PC-4018** is a part of the **E4809 CNC Boards Series** by **Okuma**.

Specifications

Certification:	AEC-Q200 (vehicle variant)	DC Resistance:	0.015?  3.80? ±20%	Dimensions:	4.0±0.2×4.0±0.2×1.8 mm (max)
Heat Rated Current:	0.17A  5.50A (?T ~40°C)	Inductance:	0.47μH  220μH ±20%/±30%	Isat Definition:	L0 drops ~30% at Isat
Material Compliance:	Pb-Free, Halogen-Free, RoHS compliant	Operating Temperature (std):	-40°C  +125°C	Operating Temperature (veh):	-55°C  +125°C
Saturation Current:	0.275A  6.00A	Self-Resonant Frequency:	4.0 MHz  151 MHz	Shielding:	Unidirectional
Solder Paste Thickness:	~0.12 mm	Test Frequency:	100 kHz @ 1V	Last Verified:	05/09/2025 9:03 PM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.