

Okuma - MDU Servo Drives

MDU-04-F



 **In Stock, Ships Fast**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping




One Year
Warranty

The **MDU-04-F** is a part of the **MDU Servo Drives Series** by **Okuma**.

Specifications

Adjustment Range:	0.5 to 70 L/min	Filtration:	25 µm, ?10 ? 75	Flow Rate:	70 L/min (18.5 U.S.GPM)
Hydraulic Fluid:	Mineral Oil Based or Equivalent	Maximum Operating Pressure:	31.5 MPa (4570 PSI)	Mounting Bolt:	M6 × 50
Mounting Surface:	ISO 4401-03-02-0-05	Port Size:	Rc 3/8	Pressure Adjustment Range:	0.7 to 21 MPa
Recommended Viscosity:	15 to 400 mm²/s	Seals:	Nitrile Rubber (Standard), Fluoro Rubber (Optional)	Temperature Range:	-15°C to +70°C (5°F to 158°F)
Type:	Modular Flow Control Valve	Weight:	2.9 kg (6.40 lbs)	Last Verified:	08/16/2025 9:09 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

