

Okuma - MDU Servo Drives

MDUF-15-2844-MA



 [Request a Quote](#)

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **MDUF-15-2844-MA** is a part of the **MDU Servo Drives Series** by **Okuma**.

Specifications

Ambient Temperature Range: 0°C to 40°C

Feedback Device: High resolution encoder (specific type per model)

Operating Frequency: 50/60 Hz

Rated Input Voltage: DC 283SPR325V

SCCR: 50kA RMS SYM

Last Verified: 06/03/2025 4:34 PM

Cooling Method:

Input Voltage:

Overload Capacity:

Rated Output Voltage:

Unit Type:

Air or liquid cooling (per configuration)
Refer to datasheet (commonly 480V 3-phase AC)

Typically up to 110-120% of rated load

AC 200V, 3-phase

Servo Spindle Drive Unit

Electrical Connections:

Mounting Configuration:

Physical Dimensions:

Rated Power:

Weight:

Standard modular plug-in type for servo drives
Designed to fit Okuma machine tool standards
Refer to datasheet for length, width, and height
Refer to datasheet (typically in kW/HP)
Refer to datasheet (in kilograms)

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

