

Okuma - MDU Servo Drives

SSU





- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer





Secure Online Checkout Free Ground Shipping

One Year Warranty

LED numeric

display, DIP

Polysulfone

0.005 Micron

switches

The **SSU** is a part of the **MDU Servo Drives Series** by **Okuma**.

Display &

Specifications

Pacteria Retention: 210¹¹ (B. Clean Water Flow Adminuta) 2.5 GPM at 30 psi COM1 RS-232, (2 bar) Communication Ports: Ethernet/RJ45

Quick Connect (CPC (APC));

(CPC (APC)); Threaded (1/2

Connections: NPSM) Dimensions: Diagnostics:

SR and ST ports,

?10? (EU/ml) P24V/IN2 input, NC/OK/DC24

Endotoxin Retention: I/O Connectivity: output Material:

75 psi (5 bar) DIN rail-mountable metal

Max Inlet Pressure:Mounting:enclosurePore Size:Replacement:Up to 3 monthsSurface Area:0.9 m²Virus Retention:?10? (PhiX-174)

05/10/2025 **Last Verified:** 1:40 PM

Shipping Options









Payment Methods









Contact Us

Old Apex Road, Cary, NC 27513, USA

J Toll Free: <u>1-888-551-3082</u>

International: <u>1-919-443-0207</u>

<u> Fax: 1-919-867-6204</u>

Email: sales@automation-factory.com