



Okuma - MPS Power Supplies

E2530-413-017-D



 [Request a Quote](#)

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **E2530-413-017-D** is a part of the **MPS Power Supplies Series** by **Okuma**.

Specifications

Cooling Method:	Natural cooling Up to 90% non-condensing	Dimensions:	35mm x 45mm	Frequency Range:	300-450 MHz
Humidity Range:		Inductance:	20 mH	Insulation:	Resin-insulated
Modulation Format:	ASK, FSK	Operating Temp.:	-10°C to 50°C	Output Power:	13 dBm max
Protection Rating:	IP20	Rated Current:	220 A	Supply Voltage:	3.3-5.0 V
Terminals:	6 (R1, R, S1, S, T1, T)	Last Verified:	06/02/2025 7:14 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.