



## Okuma - Okuma Cables

### E9101-106-011



 [Request a Quote](#)

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online  
Checkout



Free Ground  
Shipping



One Year  
Warranty

The **E9101-106-011** is a part of the **Okuma Cables Series** by **Okuma**.

## Specifications

<b>Connector Configuration:</b>	Simplex	<b>Connector Type:</b>	SENKO SN	<b>Coupling Mechanism:</b>	Push-pull with keyed alignment
<b>Dimensions:</b>	150mm x 75mm x 20mm	<b>Dust Cap:</b>	Removable	<b>Ferrule Size:</b>	Two 1.25 mm ferrules
<b>Ferrule Type:</b>	Duplex ceramic ferrule	<b>Length:</b>	3 meters	<b>Operating Temperature:</b>	-40°C to 85°C
<b>Power Consumption:</b>	3.2W	<b>Voltage Rating:</b>	5V DC	<b>Weight:</b>	250 grams
<b>Last Verified:</b>	06/05/2025 5:14 AM				

## Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: [sales@automation-factory.com](mailto:sales@automation-factory.com)

## Shipping Options



## Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.