

Okuma - Okuma Cables**E9101-I06-025-00** **Request a Quote**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer

Secure Online
CheckoutFree Ground
ShippingOne Year
Warranty

The **E9101-I06-025-00** is a part of the **Okuma Cables Series** by **Okuma**.

Specifications

| | | | | | |
|-----------------------------|--------------------------------------|-----------------------------|---|-------------------------------------|--|
| Attenuation: | 0.2 to 0.5 dB/km at 1550 nm | Bandwidth: | Up to 10 Gbps (multi-mode) 0.25 mm ² (inferred from '025' in part number) | Cable Category: | PLC / Control Cable |
| Conductor Material: | Copper | Conductor Size: | | Fire Resistance: | Fire-retardant materials |
| Insulation Material: | PVC (assumed) | Jacket Material: | PVC | Operating Temperature Range: | -20°C to +80°C (typical for industrial control cables) |
| Shielding: | Shielded for EMI reduction (assumed) | Standard Compliance: | UL/VDE compliant (assumed) | Temperature Range: | -40°C to 85°C |
| Tensile Strength: | Enhanced by strength members | Voltage Rating: | 600V AC/DC (assumed) | Water Resistance: | Gel-filled or dry-blocked designs |
| Last Verified: | 06/05/2025 10:04 AM | | | | |

Contact Us 1620 Old Apex Road, Cary, NC 27513, USA Toll Free: [1-888-551-3082](tel:1-888-551-3082) International: [1-919-443-0207](tel:1-919-443-0207) Fax: [1-919-867-6204](tel:1-919-867-6204) Email: sales@automation-factory.com**Shipping Options****Payment Methods**

Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.