

Okuma - Okuma Cables**H0026-0000-05** **Request a Quote**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer

Secure Online
CheckoutFree Ground
ShippingOne Year
Warranty

The **H0026-0000-05** is a part of the **Okuma Cables Series** by **Okuma**.

Specifications

Connector Type: Screw Terminal
Frequency: 50/60 Hz
Installation Method: Panel Mount
Storage Temperature: -20°C to +70°C
Last Verified: 06/06/2025 6:24 AM

Current: 0.5 A
Housing Material: Aluminum
Operating Temperature: -10°C to +50°C
Voltage: 100V AC

Dimensions: 150 x 75 x 50 mm
Ingress Protection Rating: IP54
Power Consumption: 50 W
Weight: 2.5 kg

Contact Us 1620 Old Apex Road, Cary, NC 27513, USA Toll Free: [1-888-551-3082](tel:1-888-551-3082) International: [1-919-443-0207](tel:1-919-443-0207) Fax: [1-919-867-6204](tel:1-919-867-6204) Email: sales@automation-factory.com**Shipping Options****Payment Methods**

Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.