

Okuma - Okuma Cables

H0120-0008-17



 **In Stock, Ships in 3-5 Days**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **H0120-0008-17** is a part of the **Okuma Cables Series** by **Okuma**.

Specifications

Coolant Tank Capacity:	230 L (60.8 gallons)	Frequency:	50/60 Hz	Guideway Type:	3-axis linear guide
Machine Height:	2,750 mm (108.27 in)	Machine Mass:	7,500 kg (16,500 lb)	Max Tool Length/weight:	300 mm / 8 kg (11.81 in / 18 lb)
Required Total Power:	22 kVA (8,000 min-1); 37 kVA (12,000 and 15,000 min-1)	Spindle Drive Power:	22/18.5 kW (30/24.67 hp)	Spindle Speed:	50 to 8,000 rpm
Table Load Capacity:	900 kg (1,980 lb)	Table Size:	560 x 1,300 mm (22.05 x 51.18 inches)	Tool Storage Capacity:	20 tools (up to 32 optional)
Voltage:	200 VAC ±10%	Voltage Protection Level:	IP 54	Working Area:	560 x 1,300 mm (22.05 x 51.18 inches)
Last Verified:	12/12/2025 6:47 PM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.