



Okuma - Okuma Cables

PE60111261



 **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PE60111261** is a part of the **Okuma Cables Series** by **Okuma**.

Specifications

Climatic Category:	25/85/21	Communication Interface:	RS485	Connection Type:	Screw Terminals
Core Material::	Glass fiber	Dimensions:	150 x 100 x 50 mm	Efficiency:	92%
Humidity Range:	5% to 95% non-condensing	Input Voltage Range:	20-40V DC	Maximum Power:	120 W
Mounting Type:	Panel Mount	Operating Temperature:	-20°C to 85°C	Output Current:	5 A
Output Voltage:	24V DC	Protection Rating:	IP65	Weight:	3.2 kg
Last Verified:	06/06/2025 4:03 AM				

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.