



Okuma - Okuma Cables

PE777-11114-01



 **Request a Quote**

- ☒ Get a Quote in 5 minutes
- ☒ Parts ship in as little as 24 hours
- ☒ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **PE777-11114-01** is a part of the **Okuma Cables Series** by **Okuma**.

Specifications

Connection Type:	3-wire, PVC cable	Current Consumption:	<10 mA	Enclosure Rating:	IP67
Housing Material:	Brass, Nickel-Plated	Max Load Current:	200 mA	Operating Voltage:	10-30 VDC
Output Function:	NO (Normally Open)		PNP	Protection Circuits:	Short-circuit and overload protection
Sensing Distance:	4 mm	Output Type:	PNP	Temperature Range:	-25°C to +70°C
Thread Size:	M12x1	Switching Frequency:	800 Hz		
		Last Verified:	08/16/2025 10:43 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.