

Okuma - OSP CNC Monitors

OSP-U100M



 **In-Stock, Ships 3-5 Days**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **OSP-U100M** is a part of the **OSP CNC Monitors Series** by **Okuma**.

Specifications

Accuracy Ambient Humidity Max:	75% RH (20°C)	Accuracy Ambient Humidity Min:	40% RH (20°C)	Accuracy Ambient Temp Max:	25°C
Accuracy Ambient Temp Min:	17°C	Control Axis:	Up to 24 axes (simultaneous control up to 14 axes)	Data Backup:	Internal flash memory, USB support
Dimensions (control Unit):	Typically 430mm x 570mm x 150mm (varies by cabinet)	External Interface:	RS-232C serial, DNC, CF card	Initial Rs-232 Baud Rate:	600 bps
Input Frequency:	50/60 Hz	Max Operating Altitude:	1000 m	Max Rs-232 Baud Rate:	19200 bps
Networking:	Ethernet (100Base-TX/10Base-T), USB	Operating Humidity Max:	95% RH	Operating Humidity Min:	30% RH
Operating Temp Max:	40°C	Operating Temp Min:	0°C	Operating Temperature:	0°C to 40°C
Operation Panel:	Ergonomic design; customizable soft keys	Power Supply:	200-240V AC, 50/60Hz	Primary Input Voltage:	200 V AC
Program Storage Capacity:	500MB or more	Ready Wait Time Max (rs-232):	9990 s	Spindle Motor:	4 (CNC, CNC) Vector high-speed spindle supported

Contact Us

1620 Old Apex Road, Cary, NC 27513, USA

Toll Free: [1-888-551-3821](tel:1-888-551-3821) AC Servo Motor, OKUMA BL Motor

Service: [1-919-443-0207](tel:1-919-443-0207)

Fax: [1-919-867-6204](tel:1-919-867-6204) CNC Controller

Last Verified: 05/24/2026 3:27 AM
Email: sales@wakeindustrial.com

Shipping Options



Payment Methods



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.