

Sanyo Denki - BL Super Servo Amplifiers

20BA075FFW43



 **Request a Quote**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **20BA075FFW43** is a part of the **BL Super Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Cooling Method:	Passive	Dimensions:	55×120×110 mm (W×H×D)	Fieldbus Interfaces:	EtherCAT (100 Mbps), Ethernet (10/100/1000 Mbps)
Humidity Range:	10% ^{SPR} 95% non-condensing	I/O Power Supply:	24 VDC (19.2 ^{SPR} 30 V), 20 mA	Input Power Supply:	24 VDC (19.2 ^{SPR} 30 V), 0.8 A
Mass:	300 g	Max Controllable Axes:	8 axes	Motion Control:	electronic cam & electronic gear
Operating Altitude:	Up to 2,000 m	Operating Temperature:	0 to 55°C	Other Interfaces:	RS-485, USB 2.0
Power Consumption:	19.2 W	Protocols:	Modbus TCP, OPC-UA	Robot Control:	Cartesian, SCARA & parallel link
Sequence Control:	supported	Shock Resistance:	147 m/s ² , 11 ms (JIS B 3502)	Storage Temperature:	-40 to 70°C
Vibration Resistance:	3.5 mm (5 ^{SPR} 8.4 Hz); 10 m/s ² (8.4 ^{SPR} 150 Hz) per JIS B 3502	Last Verified:	06/03/2025 2:03 AM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

