

Sanyo Denki - BL Super Servo Amplifiers

20BA150FFWB4B



 **In Stock, Ships Today**

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **20BA150FFWB4B** is a part of the **BL Super Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Ambient temperature range:	0 ^{SPR} 55 °C	Control functions:	Seq.; motion (cam/gear; lin./circ.); robot ctrl.	Cooling method:	Passive
Digital I/O:	16 inputs (24 VDC); 8 outputs (19.2 ^{SPR} 30 VDC, 0.5 A)	Dimensions (W×H×D):	55×120×110 mm	G-code support:	Supported (SMC100-A)
I/O power supply:	24 VDC, 20 mA	IEC 61131-3 languages:	IL, ST, LD, FBD, SFC, CFC	Input power supply:	24 VDC (19.2 ^{SPR} 30 VDC), 0.8 A
Mass:	300 g	Max controllable axes:	8 axes	Motion control cycle:	2 ^{SPR} 16 ms
Network interfaces:	EtherCAT; Ethernet (10/100/1000Mbps); RS-485 (9.6 ^{SPR} 115 kbps)	Operating/storage humidity:	10 ^{SPR} 95% (non-condensing)	Power consumption:	19.2 W
Robot control cycle:	8 ^{SPR} 16 ms	Shock resistance:	147 m/s ² , 11 ms (JIS B 3502:2011) 3.5 mm amplitude, 5 ^{SPR} 8.4 Hz	Storage temperature range:	-40 ^{SPR} 70 °C
USB interface:	USB 2.0	Vibration resistance:	(JIS B 3502:2011)	Last Verified:	06/04/2025 1:15 AM

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

