

Sanyo Denki - BL Super Servo Amplifiers

27BA100FXT17



 **Request a Quote**

- ✓ Get a Quote in 5 minutes
- ✓ Parts ship in as little as 24 hours
- ✓ Up to half the cost of the manufacturer



Secure Online
Checkout



Free Ground
Shipping



One Year
Warranty

The **27BA100FXT17** is a part of the **BL Super Servo Amplifiers Series** by **Sanyo Denki**.

Specifications

Ambient operating temperature:	0 to 55°C	Cooling method:	Passive	Digital input voltage:	24 VDC rated
Digital inputs:	16 points	Digital output max current:	0.5 A/point	Digital output voltage range:	19.2 to 30 VDC
Digital outputs:	8 points	Dimensions (W×H×D):	55×120×110 mm	Ethernet protocols:	Modbus TCP, OPC-UA (10/100/1000 Mbps)
Interface (EtherCAT):	Master, 100 Mbps	Mass:	300 g	Max controllable axes:	8
Power consumption:	19.2 W	Power supply current:	0.8 A main, 20 mA I/O	Power supply voltage:	24 VDC
Shock resistance:	147 m/s ² peak, 11 ms	Storage temperature:	-40 to 70°C	Supported programming languages:	IEC 61131-3, G-code
Vibration resistance:	3.5 mm (5 to 8.4 Hz), 10 m/s ² (8.4 to 150 Hz)	Last Verified:	08/22/2025 2:01 PM		

Contact Us

 1620 Old Apex Road, Cary, NC 27513, USA

 Toll Free: [1-888-551-3082](tel:1-888-551-3082)

 International: [1-919-443-0207](tel:1-919-443-0207)

 Fax: [1-919-867-6204](tel:1-919-867-6204)

 Email: sales@automation-factory.com

Shipping Options



Payment Methods

