

Sanyo Denki - BL Super Servo Amplifiers

60BA050SXW02



<table-of-contents> Request a Quote

- Get a Quote in 5 minutes
- Parts ship in as little as 24 hours
- ☑ Up to half the cost of the manufacturer



Free Ground Shipping One Year Warranty

The 60BA050SXW02 is a part of the BL Super Servo Amplifiers Series by Sanyo Denki.

Specifications

Ambient Operating Temperature:	0°C to 55°C	Communication Cycle Time:	2 to 16 ms (typical)	Communication Interface:	EtherCAT 100 Mbps fieldbus
Cooling Method:	Passive	Digital Inputs:	16 inputs (24 VDC, common type)	Digital Outputs:	8 outputs (19.2- 30 VDC, 0.5 A/point)
Dimensions	55×120×110 mm	Digital inputor	24 VDC, 20 mA; 19.2-30 VDC	Digital Outputor	24 VDC, 0.8 A; 19.2-30 VDC
(W×H×D):		I/O Power Supply:	range	Main Power Supply:	range NEC-based real-
Mass:	300 g	Maximum Controllable Axes:	Up to 8 axes	Microprocessor Type:	time control processor
Operating Humidity:	10% to 95% (non- condensing)	Power Consumption:	19.2 W	Shock Resistance:	147 m/s² peak, 11 ms duration
Storage Temperature:	-40°C to 70°C	Last Verified:	06/06/2025 1:58 AM		

Contact Us

- ♀ 1620 Old Apex Road, Cary, NC 27513, USA
- J Toll Free: <u>1-888-551-3082</u>
- International: <u>1-919-443-0207</u>
- 둼 Fax: <u>1-919-867-6204</u>
- Email: <u>sales@automation-factory.com</u>

Shipping Options



Automation Factory sells factory new and pre-owned surplus products and maintains channels to procure supply. Automation Factory is not affiliated with nor an authorized distributor or representative of any manufacturers, brands or products listed. Designated trademarks, brand names, and brands appearing herein are the property of their respective owners.